

PIPES AND CONNECTORS

1.4

Adjustable Elbows

Description

Metal Zinc's adjustable elbows are used for low pressure applications and can be adjusted to any degree.

Features

Meets SMACNA requirements (3rd Edition Section 3.29 Figure 3-4)

Pressure rating (+/-2 water gauge)

Welded seam for added strength and low leakage

Packaged in trays for efficient field handling and keeping elbows enclosed for cleanliness



Standard Construction

Manufactured using 26 and 30-gauge ASTM material

Manufactured from one piece of sheet metal through 10"

Optional Construction

24-gauge galvanized steel

Agion (antimicrobial coating)

Aluminum

Galvanneal (paint grip)

PCD

Stainless steel 304 and 316

Packaging

Metal Zinc Part Number	Size A Inches	Gauge	Tray Quantity	Pallet Quantity
SME3-90	3	26	64	2,048
SME4-90	4	26	36	1,152
SME5-90	5	26	25	550
SME6-90	6	26	16	320
SME7-90	7	26	12	240
SME8-90	8	26	9	180
SME9-90	9	26	6	96
SME10-90	10	26	5	80
SME12-90	12	26	4	64
SME14-90	14	26	MTO	Made to Order
SME16-90	16	26	MTO	Made to Order
SME3-90-30	3	30	64	2,048
SME4-90-30	4	30	36	1,152
SME5-90-30	5	30	25	550
SME6-90-30	6	30	16	320
SME7-90-30	7	30	12	240
SME8-90-30	8	30	9	180
SME9-90-30	9	30	6	96
SME10-90-30	10	30	5	80

