



Product Data Sheet

Q7721 Air Assist LOW VOC Contact Adhesive Fast Tack, Water-Resistant

Q7721 Air Assist LOW VOC Contact Adhesive

Features

- High Strength, High Shear
- Quick Tack Formula
- No Ozone Depleting Substances
- Water-Resistant Bond
- Great for Multiple Substrates

Description

Quality Aerosols Q7721 Air Assist LOW VOC Adhesive is a high strength, high shear, fast tack adhesive developed exclusively to work like a pressure pot system. It can be used on wood, particle board, plastic, fiberglass insulation and many other substrates. It has a quick tack with high solids and a water resistant bond.

Applications

Q7721 is used for the permanent bonding of wood, particle board, plywood, FRP board, plastics, fiberglass insulation and many other substrates.

Product Usage

Q7721 Adhesive is designed as a two surface bonding application. Both surfaces need to be dry and clean of oil and debris. Spray an even coat of adhesive to cover 80%-100% of the surfaces. Allow solvents to dry 3-5 minutes until the adhesive becomes tacky. For porous surfaces it is recommended to apply a second coat after the first coat has become tacky. Put the coated surfaces together and apply uniform pressure. Full adhesive strength will be reached in 24 hours.

Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk and canister products should be kept off the floor.

Product Specifications

Color	Clear to Yellow
Solids	32.1% +/- 2%
VOC g/L	210 g/L
Bonding Range	3-60 hours
Dry/Tack Time	3-5 minutes
Spray Pattern	Determined by used
Sizes Offered	9#, 30#, 135#, 270#
Warranty Period	1 year from manufacture date
Square Feet Coverage	approx 47 ft ² @ 2.5g

Note: all results are based on 2.5g dried glue/ft²

Recommended Spray Gun	Binks 2100, Air Cap 66SD-3, Fluid Nozzle 66SS, Needle 565
-----------------------	---



**QUALITY
AEROSOLS**

For More Innovative Products from Quality Aerosols
Visit us at www.qualityaerosols.com