

Plumbing Selection Chart

HANGER NO.	STEEL-PLASTIC	COPPER TYPES	REFRIGERATION	MAX LOAD
1129-(MM RANGE)	SCH. 40 & 80	K, L, M, DWV	COPPER	
1129-12-16	1/4"	3/8"-1/2"	1/2"-5/8"	170
	0.54	.500-.625	.500-.625	
1129-17-20	3/8"	5/8"	3/4"	195
	0.675	0.75	0.75	
1129-21-24	1/2"	3/4"	7/8"	215
	0.84	0.875	0.875	
1129-25-29	3/4"	1"	1-1/8"	315
	1.05	1.125	1.125	
1129-30-34	1"			320
	1.315			
1129-35-38		1-1/4"	1-3/8"	342
		1.375	1.375	
1129-40-44	1-1/4"	1-1/2"	1-5/8"	365
	1.66	1.625	1.625	
1129-48-54	1-1/2"	2"	2-1/8"	380
	1.9	2.125	2.125	
1129-56-63	2"			410
	2.375			
1129-66-76	2-1/2"	2-1/2"	2-5/8"	500
	2.875	2.625	2.625	
1129-79-93	3"	3"-3-1/2"	3"-3-1/2"	600
	3.5	3.125-3.625	3.125-3.625	
1129-101-115	3-1/2" to 4"	4"	4"	950
	4.000-4.500	4.125	4.125	

Electrical Selection Chart

HANGER NO.	ELECTRIC	ELECTRIC	ELECTRIC
1129-(MM RANGE)	EMT	HEAVY WALL	IMC
1129-17-20	1/2"		
	0.706		
1129-21-24	3/4"	1/2"	1/2"
	0.922	0.84	0.815
1129-25-29		3/4"	3/4"
		1.05	1.029
1129-30-34	1"	1"	1"
	1.163	1.315	1.29
1129-35-38	1-1/4"		
	1.51		
1129-40-44	1-1/2"	1-1/4"	1-1/4"
	1.74	1.66	1.638
1129-48-54		1-1/2"	1-1/2"
		1.9	1.883
1129-56-63	2"	2"	2"
	2.197	2.375	2.36
1129-66-76	2-1/2"	2-1/2"	2-1/2"
	2.875	2.875	2.857
1129-79-93	3"	3"	3"
	3.5	3.5	3.5
1129-101-115	4"	4"	4"
	4.5	4.5	4.5

NOTE: Fractional numbers reflect nominal pipe diameter, decimal numbers reflect actual O.D. in inches.

SNAP-N-STRUT PRODUCTS MADE WITH NYLON 6/6 HAVE AN EXCELLENT RATING FOR RESISTANCE TO THE FOLLOWING CHEMICALS:

Acetic Acid (5%), Acetone, Ammonia, Ammonium Chloride (10%), Amyl Acetate, Barium Sulphide (10%), Benzene, Boric Acid (10%), Butylene Glycol, Camphor, Carbon Disulphide, Carbon Tetrachloride, Cyclohexane, Cyclohexanol, Dimethyl Formamide, Diesel Oil, Dioctyl Phthalate, Dioxan, Edible Oils, Ethanol (90%), Ether, Ethyl Acetate, Ethylene Chloride, Freon (12%), Formaldehyde (30%), Gasoline, Gasohol W/10% Ethanol, Glycerine, Heptane, Hexane, Lactic Acid (10%), Linseed Oil, Magnesium Chloride (10%), Methanol, Methyl Acetate, Methyl Ethyl Ketone, Milk, Mineral Oil, Parafin, Pechlorethylene, Potassium Bromide (10%), Potassium Carbonate (60%), Potassium Hydroxide (50%), Potassium Hydroxide (10%), Potassium Nitrate (10%), Propanol, Salicyclic Acid, Silicone Oils, Sodium Bicarbonate Aq. (50%), Sodium Bisulphite, Sodium Carbonate (10%), Sodium Chloride (10%), Sodium Hydroxide (10% & 50%), Sodium Nitrate (10%), Sodium Phosphate (90%), Sodium Sulphate (90%), Sulphur, Tataric Acid (10%), Tetrachlorethylene, Toluene, Turpetine, Urea, Vaseline, Water, Wax Molten, Wine and Xylene

SNAP N STRUT PRODUCTS MADE WITH NYLON 6/6 HAVE A GOOD RATING FOR RESISTANCE OF THE FOLLOWING CHEMICALS:

Butyl Acetate, Calcium Chloride (10%), Clorox Bleach, Formaldehyde (40%), Fruit Juices, Hydrogen Sulfide, Isopropyl Alcohol, and Tar

UL LISTED for flame, thermal, and support properties. Also rated for air returns and plenums.	AMERICAN MADE pipe hangers.
THERMAL PROPERTIES – Snap-N-Strut hangers can handle extreme temperatures.	GREATER LOADS – Snap-N-Strut hangers have large safety factors.
ABSORBS VIBRATION and acts as a cushion between the piping and its supports.	ADJUSTABILITY – Different size pipes can be nestled together for a snug fit.
CORROSION-PROOF – With our non-metallic design, there is no need to isolate copper tubing.	NO HARDWARE REQUIRED – Snap-N-Strut hangers are self-gripping.
UV RATED – Black nylon parts can be used in direct sunlight outdoors or on rooftops.	MSS SP-58 – Meets the engineering requirements of SP-58 (see Data tab).
VERSATILE hangers for many different types of jobs means less inventory is required.	SELF GRIPPING – Designed to grip the strut and prevent lateral movement.